SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

      BE IT KNOWN THAT I, HIROSHI SHIMURA, a
citizen of Japan residing at Kanagawa, Japan have
invented certain new and useful improvements in

IMAGE RECOGNITION SCHEME

of which the following is a specification:-

BACKGROUND OF THE INVENTION

    1. Field of the Invention

    The present invention relates to an image recognition scheme, and, in particular, to an image recognition scheme by which a specific pattern image can be recognized/identified/detected highly precisely.

    2. Description of the Related Art

    Concerning a color image recognition method, for example, Japanese laid-open patent application No. 8-263662 discloses a method in which, not an entire input color image is processed uniformly, but only a pattern image which is formed in accordance with a predetermined rule is attempted to be recognized highly precisely.

    According to this art, mark extraction is made by using a window for scanning 'binary image data' (in which each pixel has a value of either one of two values, for example, 0 and 1, or white and black) or through Hough transformation. However, determination as to whether or not a target image part corresponds to a predetermined mark (pattern image) to be recognized/detected may be difficult in case where a relevant image part has become unclear, i.e., a relevant figure is faint, or crushed due to some reason.

SUMMARY OF THE INVENTION

A present invention has been devised in order to solve such a problem, and, an object of the present invention is to provide a novel image recognition scheme

5   by which image recognition/identification/detection can be made highly precisely even on such an unclear image.

According to the present invention, a relevant image part is given a score according to resemblance thereof with a predetermined pattern image, and, then,

10 at a next stage, this score is reflected by a determination for pattern detection to be achieved.

For example, in case a pattern image including three marks is detected, if one mark thereof is faint by accident in an actual object predetermined image part,

15 this image part may not be determined as the predetermined pattern image even if it is originally the predetermined pattern image, in the related art.   In contrast thereto, according to the present invention, even in such a case in which only one of three marks is

20 faint or crashed, it may be extracted as a mark candidate having even a low resemblance, and, then, finally, the target image part may be correctly determined as the predetermined pattern image. Furthermore, according to the present invention, when

25 every mark candidates are nothing but of low resemblance,

the target image part is not determined as the
predetermined pattern image. Thereby, it is possible to
prevent an image part which is other than the relevant
pattern image from being erroneously determined as the
5   relevant pattern image. Thus, according to the present
invention, as a target image pattern/figure is totally
or symmetrically examined, the highly precisely
determination can be obtained.

An image recognition device according to the
10   present invention includes an extracting part extracting,
from binary image data, predetermined marks, and a
determining part determining whether or not the thus-
extracted marks form a predetermined pattern to be
recognized/detected. Specifically, the extracting part
15   includes a scoring part which cuts out a predetermined
area from the input binary image, a counting part counts
the number of black pixels and/or the number of black
pixels determined after predetermined inter-pixel
logical operation is performed, and a first scoring part
20   which gives a score on resemblance with the
predetermined mark, from the thus-counted number of
black pixels and/or inter-pixel relationship. The
determining part includes a pattern detecting part which
detects a pattern from position information on the
25   extracted marks, a second scoring part which gives a

score on resemblance on the pattern based on the score
of each mark obtained by the first scoring part, and a
decision part which finally determines from the score
obtained by the second scoring part, whether or not the
5 thus-examined target pattern is the predetermined
pattern to be recognized/detected.

Thus, according to the present invention, as
input image parts can be given scores by various manner
as to how much these image parts resemble to a
10 predetermined figure (pattern)
individually/independently, and, then, after that, a
positional relationship therebetween is examined as to
how much the positional relationship of the input image
parts resembles the same of the elements of the
15 predetermined figure to be recognized/detected, together
with a sum of the resemblances of the respective marks,
synthetically. Thereby, even when some image part may
not be satisfactorily resemble to the element of the
predetermined figure due to faint tone in printed image
20 or crash of each element there due to aging of the
printed image or the like, the predetermined figure can
be recognized when the positional relationship
therebetween is sufficiently resemble to that of the
ideal one, and, also, the sum of the scores in
25 resemblances on the respective image parts. Thus, it is

possible to positively recognize the predetermined figure, and also, positively avoid erroneous recognition, by totally, synthetically and finely examining the input image parts.

5

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and further features of the present invention will become more apparent from the following detailed description when read in conjunction

10   with the following accompanying drawings:

FIG. 1 illustrates a general configuration of one embodiment of the present invention and an operation flow thereof according to the present invention;

FIG. 2 shows an example of a pattern which

15   consists of marks to be recognized/detected by the present invention;

FIG. 3 shows an example of a mask according to the above-mentioned embodiment of the present invention to be used for measuring the number of black pixels on

20   respective areas concerning a target pattern so as to give scores on each mark extracted;

FIG. 4 shows an example of an arrangement of actual black pixels on the mask shown in FIG. 3;

FIG. 5 shows an example of an arrangement of

25   black pixels to be counted on the mask shown in FIG. 4

according to the present invention;

FIG. 6 shows another example of an arrangement of black pixels to be counted on the mask shown in FIG. 4 according to the present invention;

FIG. 7 shows another example of an arrangement of black pixels to be counted after performance of logical operation between the pixels on the mask shown in FIG. 4 according to the present invention; and

FIGS. 8 and 9 show an operation flow chart illustrating an example of processing performed by a registration part shown in FIG. 1 according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 illustrates an example of a flow of operation in the whole of an image recognition device in one embodiment of the present invention. As shown in the figure, the image recognition device includes an extracting part 20 including a logical circuit 21, a measurement part 22, and a first scoring part 23, while a determining part 30 which includes a registration part 31, a detection part 32, a second scoring part 33, and a decision part 34. The first scoring part 23 has a scoring part 23a and a score summarizing part 23b.

First, a predetermined area is extracted via a

mask 11 from a binary image (binary image data) 10 (in a step S1), and measurement part 22 counts the number of black pixels in the predetermined area defined by the mask 11, or the number of black pixels after performance

5 of logic operation between pixels using the logic circuit 21 (in steps S2 and S3). The scoring part 23a determines a score on the thus-processed area as a mark candidate from the counted number of black pixels (in a step S4) thereon, and the thus-counted scores on the

10 respective mark candidates are totaled as a resemblance value by the score summarizing part 23b (in a step S5). The registration part 31 determines the thus-processed areas of the mark candidates as marks temporarily when the areas have the resemblance value more than a

15 predetermined value (in a step S6), then, sends the coordinate values thereof to the detection part 32 (in a step S7), and, the resemblance value is sent to the second scoring part 33 (in a step S9).

The detection part 32 detects positional

20 difference between the thus-detected pattern and the predetermined pattern to be recognized/detected, determines a score on the amount of the thus-detected positional difference, and sends it to the second scoring part 33 (in a step S8). The second scoring part

25 33 summarizes the thus-obtained score on the positional

difference and the above-mentioned resemblance value on the total score of the marks detected, and determines a final resemblance value from these two factors in total, which is sent to the decision part 34 (in a step S10).

5 Then, in the decision part 34, it is determined that the thus-examined pattern is of the predetermined pattern to be recognized/detected when the thus-obtained final resemblance value is not less than a predetermined value (in a step S11).

10 It is noted that the above-mentioned mask 11 scans the entire binary image 10 in sequence, and at every time the mark is located at a position in the binary image, the above-described processing is performed on the pixels defined by the mask at the time.

15 FIG. 2 shows an example of a predetermined pattern which includes three marks (at vertexes of a triangle shown) to be recognized/detected. The mask 11 which defines areas from the binary image 10 includes a foreground part (mark) 11b including pixels forming each

20 mark, and a background part 11b including pixels acting as a background of the mark. A pattern 12 is formed by these three marks. In this example, as shown in the figure, the pattern is of the triangle, and the respective marks act as the vertexes of the triangle as

25 mentioned above. As will now be described, the

plurality of marks are given scores (resemblance with
the ideal mark), and then, whether the pattern 12 formed
by these marks on the target binary image examined is of
the predetermined pattern to be recognized/detected is
5   determined by the determination part 30.

A specific example will now be described.   In
this example, each mark is of a circle having a diameter
of 8 pixels.

FIG. 3 shows an example of the mask 11 in the
10 embodiment of the present invention, and, in the mask 11,
a target pixel 11a is one located at the center thereof,
as shown in the figure.   The foreground part 11b is
divided into a plurality of areas, i.e., a first area
through a ninth area, and reference numerals indicating
15 the number of relevant areas are given to the respective
pixels, as shown in the figure.   The background part 11c
includes two areas, i.e., an 'a' area and a 'b' area,
the same alphabets of 'a' and 'b' indicating the
relevant areas are given to the respective pixels, as
20 shown in the figure.

The mask 11 is made to move on a relevant
binary image 10, so as to scan the image 10 in a manner
in which the target pixel 11a coincides with each of all
the pixels of the relevant image 10 sequentially, pixel
25 by pixel, for example.   In each position of the mask 11

on the image 10, the black pixels existing in the foreground part 11b are counted according to a manner which will be described later.

Specifically, the measurement part 22 counts the black pixels existing in each area of the foreground part 11b. Hereinafter, $C(n)$ denotes the thus-counted number of black pixels on the n-th area, where n = 1 through 9, and also, $C(a)$ and $C(b)$ denote the numbers of black pixels in the respective area 'a' and area 'b'.

(1) For the purpose of determining whether or not the foreground part 11b is sufficiently black, the total number of black pixels Cs is calculated by the following formula (1):

$$Cs = \Sigma\ C(i) \quad \cdot\cdot\cdot (1)$$
where i = 1 through 9.

(2) For the propose of determining whether or not the background part 11c is sufficiently white, the Cx is calculated by the following formula (2):

$$Cx = C(a) + C(b) \quad \cdot\cdot\cdot (2)$$

However, this calculation by the formula (2) is not made when the above-mentioned value Cs is

sufficiently large, i.e., the foreground part 11b is
sufficiently black.

In case the above-mentioned value Cs is
sufficiently large, i.e., the foreground part 11b is
5   sufficiently black, Cx is calculated rather by the
following formula (3):

$$Cx = (C(b) - 2) \times 2 \quad \cdots \quad (3)$$

10   In case where the entire binary image 10 is
black, each mark (black circle) may have been crushed,
so that the mark becomes larger. Thereby, it may be
difficult to distinguish the case from a case a shape
other than a circle has a black background. In order to
15   solve this problem, only in case the foreground part 11b
is sufficiently black, the black pixels rather in the
area 'b' which is not adjacent to the foreground part
11b are counted as in the formula (3) assuming that the
crush of the mark occurs so that the mark may have been
20   somewhat enlarged. Thereby, even in such a case, the
mark can be left as a candidate for the subsequent stage.
It is noted that, "-2" in the above-mentioned formula
(3) is only for numerical adjustment.

(3) In order to determine symmetry of the
25   target mark, Csym is calculated which is the number of

black pixels obtained by performing exclusive OR (XOR) operation between pixels located left-and-right symmetrical positions with respect to the vertical center line on the mask 11 for the areas 1 through 9.

5 That is, when both the symmetrical pixels are black or white, the result of XOR is white, while, when only one thereof is white, the result is black. In other words, the XOR result becomes black only when the values of both the symmetrical pixels are different. Accordingly,

10 Csym becomes larger as the target mark becomes more different from a left-and-right symmetrical shape.

FIG. 4 shows an example of arrangement of black pixels on the mask 11 shown in FIG. 3, and halftone portions (portions in deep gray) represent

15 black pixels, respectively, in the figure. According to the example of arrangement of the black pixels shown in FIG. 4, the respective numbers Cs and Cx of black pixels and Csym are obtained by counting. FIGS. 5, 6, and 7 show examples of arrangement of black pixels to be

20 counted.

As shown in FIG. 5, when the black pixels in the areas 1 through 9 on the foreground part 11b (portions in deeper gray) are counted, Cs = 41. As shown in FIG. 6, when the black pixels in the areas 'a'

25 and 'b' on the background part 11c (portions in deeper

gray) are counted, Cx = 7. Similarly, as shown in FIG.
7, when the exclusive OR operation is performed between
each pair of left-and-right symmetrical pixels with
respect to the vertical center line on the foreground
5   part 11b, and then, the black pixels obtained by the
operation (portions in deeper gray) are counted, Csym =
7.

Then, in the above-mentioned first scoring
part 23, the counting part 23a converts the thus-
10   obtained numbers Cs, Cx and Csym into various scores
which express characters of the target mark examined, as
follows:

(1) The following two-dimensional table 1, for
example, is used for converting the relationship in the
15   number of black pixels between Cs and Cx into a score
Psx which expresses how the target mark is resemble with
the predetermined circle.

Table 1   (for Psx)

Cs / Cx	··· 11	12 ··· 9	20 ··· 27	28 ··· 35	36 ···
0 ··· 7	−1	22	27	29	30
8 ··· 15	−1	8	25	28	29
16 ··· 23	−1	−1	8	23	24
24 ···	−1	−1	−1	12	25

20

Specifically, according to table 1, as Cs is larger and

Cx is smaller, the score becomes higher.

(2) The following two-dimensional table 2, for example, is used for converting the relationship between the numbers of black pixels C(1) through C(9) in the respective first through ninth areas, based on such a relationship as that, as lacks (i.e., white) in the foreground part 11b are fewer, the target mark is more resemble to the predetermined circle, where Pc expresses the score indicating the continuity of the foreground part 11b.

Table 2 (for Pc)

C(1) through C(9) in number	Score Pc
Every one is not less than 4	7
Only one is less than 4	3
Each of only one pair of adjacent ones is less than 4	2
The other cases	-1

Specifically, according to table 2, as the number in every area is larger, the score becomes higher.

(3) The score Psym represents symmetry, and, based on such a supposition that, as the symmetry in the foreground 11b is higher, the target mark is more resemble to the predetermined circle, the score Psym is obtained from the following two-dimensional table 3 as the relationship between the above-mentioned number Csym

of black pixels and the number Cs of black pixels.

Table 3 (for Psym)

Cs Csym	0 … 7	8 … 15	16 … 23	24 …
0 … 3	−1	−1	−1	−1
4 … 7	−1	2	1	−1
8 … 11	−1	1	2	1
12 …	−1	−1	2	3

5   (4) The rotatioality is represented by Pac, and, by using the following two-dimensional tables 4, (A) and (B), supposing that, as the periodicity in the circumferential direction is smaller in the target mark, the target mark is more resemble to the predetermined

10   circle, differences between the numbers C(1) through C(9) of black pixels in the respective first through ninth areas are converted into the score Pac. This determination is made in order to prevent halftone dots from being erroneously determined as the predetermined

15   circle. For example, for examining the periodicity in 45 degrees and the periodicity in 90 degrees, the following formulas (4) and (5) are used. The formula (4) calculates differences in numbers of black pixels between areas having positional relationship of 45

20   degrees, and then, sums them. The thus-obtained sum is referred to as Ca45. Similarly, the formula (5)

calculates differences in numbers of black pixels between areas having positional relationship of 90 degrees, and then, sums them. The thus-obtained sum is referred to as Ca90.

5

$$Ca45 = |C(1) - C(2)| + |C(2) - C(3)|$$
$$+ |C(3) - C(4)| + |C(4) - C(5)|$$
$$+ |C(5) - C(6)| + |C(6) - C(7)|$$
$$+ |C(7) - C(8)| + |C(8) - C(1)| \quad \cdots \quad (4)$$

10

$$Ca90 = |C(1) - C(3)| + |C(2) - C(4)|$$
$$+ |C(3) - C(5)| + |C(4) - C(6)|$$
$$+ |C(5) - C(7)| + |C(6) - C(8)|$$
$$+ |C(7) - C(1)| + |C(8) - C(2)| \quad \cdots \quad (5)$$

15

If the target mark is of an ideal circle, the number of black pixels of each area is equal to every others, and, thus, $C(n) = C(m)$ where n and m are every ones of 1 through 8. As a result, $Ca45 = Ca90 = 0$.
20 However, $Ca45 \gg 0$ and $Ca90 = 0$ when the target mark comprises halftone dots present in vertical and horizontal directions.

With regard to the following table 4 also mentioned above, it is noted that, the score in each
25 place indicated by (B) in table (A) is obtained by using

table (B).

Table 4 (for Pac)

(A)

Ca45 \ Ca90	0 … 3	4 … 7	8 … 11	12 …
0 … 3	(B)	(B)	(B)	(B)
4 … 7	-1	(B)	(B)	(B)
8 … 11	-1	-1	(B)	(B)
12 …	-1	-1	-1	(B)

(B)

Ca45 \ Cs	… 11	12 … 19	20 … 27	28 … 35	36 …
0 … 3	5	5	5	5	5
4 … 7	5	5	5	5	4
8 … 11	5	5	5	4	3
12 … 15	5	5	5	2	1
16 …	5	5	3	-1	-1

The first scoring part 23 has the score
summarizing part 23b, which calculates a final mark
resemblance Pel from the various scores obtained by the
counting part 23a as described above. The following
formula (6) and formula (7), for example, are used for
calculating the final resemblance Pel.

Pel = 0, when at least one of Psx, Pc, Psym, and
Pac, mentioned above, is -1   ... (6)

Pel = Psx + Pc + Psym + Pac, in any other cases

                                               ... (7)

However, the calculation formula is not
limited thereto, and, subtraction type one may be used,
instead, such as Pel = Psx - Pc -Psym - Pac, depending
on scoring manners employed by the counting part 23a.
The thus-calculated Pel is sent to the registration part
31.

The registration part 31 sends, to the
detection part 32, only the target marks each having the
mark resemblance Pel not less than a predetermined value.
However, when the distances between the target marks are
not longer than a predetermined number of pixels, only
the target mark having the highest score thereof is sent
to the detection part 32. This is because a plurality
of marks present within the predetermined number of
pixels are to be prevented from being extracted.
Further, what is more important is, it is necessary to
determine more accurate mark position by selecting the
mark having the highest score (highest reliability).

FIGS. 8 and 9 show an operation flow chart

illustrating an example of processing performed by the registration part 31 according to the present invention.

First, a counter counting the number of pixels CNT(x) and a score buffer storing the mark score PNT(x) are prepared. All the initial values are 0. First, the x-coordinate and y-coordinate are set to 0 (in steps S21 and S22). A temporarily extracted mark is given a score, which is then represented by p(x,y) in a step S23, and, then, p(x,y) is compared with the mark score PNT(x) previously stored in the score buffer (in a step S25). Then, one of them having the larger score is stored in the score buffer. That is, when p(x,y) is smaller than PNT(x), PNT(x) is left in the score buffer as it is, and CNT(x) is incremented by one in a step S26. When p(x,y) is not smaller than PNT(x), p(x,y) is stored in the score buffer as the mark score, and CNT(x) is initialized into 0 in a step S27. Then, it is determined whether or not the current x value is the last value in x-coordinate, in a step S28. When the current x value is not the last value in x-coordinate, the x value is incremented by one in a step S29, and the operation is returned into the step S23.. When the current x value is the last value in x-coordinate, the x value is initialized into 0 in a step S30, and the operation is continued into a step S31.

Then, an inter-mark distance I is set into 1
in a step S31. Then, the score buffers are scanned, and,
the mark scores of the marks present less than a
predetermined minimum permissible distance from one

5   another are compared. That is, the mark scores PNT(x)
and PNT(x+I) are compared by one another in a step S32.
Then, when PNT(x) is larger than PNT(x+I), PNT(x) is
left as it is, while PNT(x+I) is set into 0 in a step
S33. Then, the inter-mark distance I is compared with

10 the predetermined minimum permissible distance in a step
S35. Then, when the distance I is not larger than the
permissible value, the distance I is incremented by one
in a step S36. When the distance I is larger than the
permissible value, the operation is continued to a step

15 S37. When PNT(x) is not larger than PNT(x+I) in the
step S32, PNT(x+I) is left as it is, while PNT(x) is set
into 0 in a step S34, and then, the operation is
continued into the step S37.

In the step S37, it is determined whether or

20 not the current x value is the last value in x-
coordinate. When it is not the last in x-coordinate,
the x value is incremented, and, then, the operation is
returned into the step S31. When it is the end in x-
coordinate in the step S37, the x value is initialized

25 into 0, and the operation is continued into a step S40,

in a step S39.

Then, the above-mentioned counters are scanned, and, it is determined whether each counter value CNT(x) is not less than a predetermined minimum permissible distance in a step S40. When CNT(x) is not less than the minimum permissible distance, the relevant coordinate values and score are registered as a mark candidate to be sent to the detection part 32 in a step S41. When CNT(x) is less than the minimum permissible distance, the operation is continued into a step S43. After the coordinate values and score are sent to the detection part in the step S41, each of PNT(x) and CNT(x) is initialized into 0 in a step S42, and, then, it is determined whether the current x value is the last in x-coordinate in a step S43. When it is not the last in x-coordinate, the x value is incremented by one in a step S44, and the operation is returned into the step S40. When it is the last in x-coordinate, it is determined whether or not the current y value is the last in y-coordinate in a step S45. When it is not the last in y-coordinate, the y value is incremented by one in a step S46, and the operation is returned into the step S22. When it is the last in y-coordinate, the operation is finished.

A specific example of operation of the

registration part described above with reference to FIGS.
8 and 9 will now be described.

First, the above-mentioned minimum permissible
distance in the step S34 is "3" while the same in the
5   step S40 is also "3".

It is assumed that the score p(x,y) is as
follows, for example:

```
X=      1  2  3  4  5  6  7  8
10      . . . . . . . . . . . . . . . . . . . . . . . . . . . .

Y=1 ...0  0  0  0  0  0  0  0...

Y=2 ...0  0  0  0 15  0  0  0...

Y=3 ...0  0  0 18 20  0  0  0...

Y=4 ...0  0  0  0 12  0  0  0...

15  Y=5 ...0  0  0  0  0  0  0  0...

Y=6 ...0  0  0  0  0  0  0  0...

Y=7 ...0  0  0  0  0  0  0  0...

        . . . . . . . . . . . . . . . . . . . . . . . . . . . .
```

20   Then, until Y=2, X=4 from the initial state:

```
X=        1  2  3  4  5  6  7  8
PNT(X) = 0  0  0  0  0  0  0  0
CNT(X) = 0  0  0  0  0  0  0  0
```

25

Then, when Y=2, X=5,

(S25) becomes No since PNT(5)(=0)<p(5,2)(=15), then

PNT(5)←p(5,2), CNT(5)←0 (S27), thus,

5 X=   1 2 3 4 5 6 7 8

PNT(X) = 0 0 0 0 15 0 0 0

CNT(X) = 0 0 0 0 0 0 0 0

(S32) becomes No as PNT(5)(=15)>PNT(5+I)(=0) when X=5,

10 then PNT(5+I)←0, CNT(5+I)←0(S33), while (S32) becomes

Yes as PNT(X)(=0)=PNT(X+I)(=0) when X≠5 then PNT(X)←0,

CNT(X)←0 (in any case, PNT, CNT do not change).

Then, (S40) becomes No, as CNT(X)(=0)<3 (PNT, CNT do not

change).

15   Then, when Y=3, X=4

(S25) becomes No as PNT(4)(=0)<p(4,3)(=18), then

PNT(4)←p(4,3), CNT(4)←0 (S27), and, thereby,

X=   1 2 3 4 5 6 7 8

20 PNT(X) = 0 0 0 18 15 0 0 0

CNT(X) = 0 0 0 0 0 0 0 0

Then, when Y=3, X=5,

(S25) becomes No as PNT(5)(=15)<p(5,3)(=20), then

25 PNT(5)←p(5,3), CNT(5)←0 (S27), and, thereby,

```
X=        1   2   3   4   5   6   7   8
PNT(X) = 0   0   0  18  20   0   0   0
CNT(X) = 0   0   0   0   0   0   0   0
```

5   (S32) becomes Yes as PNT(X) (=0)=PNT(X+I) (=0) when X<4,

and, thereby, PNT(X)←0, CNT(X)←0 (S34) (PNT, CNT do not

change), while, (S32) becomes Yes as

PNT(4) (=18)<PNT(5) (=20) when X=4 and I=1, and, thereby,

PNT(4)←0, CNT(4)←0 (S34), and, thereby

10

```
X=        1   2   3   4   5   6   7   8
PNT(X) = 0   0   0   0  20   0   0   0
CNT(X) = 0   0   0   0   0   0   0   0
```

15 (S32) becomes No as PNT(5) (=20)>PNT(5+I) (=0) when X=5,

and, thereby, PNT(5+I)←0, CNT(5+I)←0 (S33) (PNT, CNT do

not change), while, (S32) becomes Yes as

PNT(X) (=0)=PNT(X+I) (=0) when X>5, and, thereby, PNT(X)←0,

CNT(X)←0 (S34) (PNT, CNT do not change).

20 (S40) becomes No as CNT(X) (=0)<3 (PNT, CNT do not

change).

            Then, when Y=4, X=5,

    (S25) is Yes as PNT(5) (=20)>p(5,4) (=12), then,

25 CNT(5)←CNT(5)+1 (S26), and, thereby,

```
X=       1  2  3  4  5  6  7  8
PNT(X)=  0  0  0  0 20  0  0  0
CNT(X)=  0  0  0  0  1  0  0  0
```

5   (S32) becomes Yes as PNT(X)(=0)=PNT(X+I)(=0) when X<5,
    then PNT(X)←0, CNT(X)←0 (S34), while (S32) becomes No as
    PNT(5)(=20)>PNT(5+I)(=0) when X=5, then PNT(5+I)←0,
    CNT(5+I)←0 (S33).
    (S32) becomes Yes as PNT(X)(=0)=PNT(X+I)(=0) when X>5,

10 then PNT(X)←0, CNT(X)←0 (S34).
    (Any case, PNT, CNT do not change.)
    (S40) becomes No as CNT(X)(=0)<3 (PNT, CNT do not
    change).
              Then, when Y=5, X=5,

15 (S25) is Yes as PNT(5)(=20)>p(5,5)(=0), and, thereby,
    CNT(5)←CNT(5)+1 (S26), and, thus


```
X=       1  2  3  4  5  6  7  8
PNT(X)=  0  0  0  0 20  0  0  0
```
20 ```
CNT(X)= 0 0 0 0 2 0 0 0
```

    (S32) becomes Yes as PNT(X)(=0)=PNT(X+I)(=0) when X<5,
    then PNT(X)←0, CNT(X)←0 (S34), while (S32) becomes No as
    PNT(5)(=20)>PNT(5+I)(=0) when X=5, then PNT(5+I)←0,

25  CNT(5+I)←0 (S33).

(S32) becomes Yes as PNT(X)(=0)=PNT(X+I)(=0) when X>5,

then PNT(X)←0, CNT(X)←0 (S34).

(Any case, PNT, CNT do not change.)

(S40) becomes No as CNT(X)(=0)<3 (PNT, CNT do not

5   change).


        Then, when Y=6, X=5,

(S25) is Yes as PNT(5)(=20)>p(5,6)(=0), and, thereby,

CNT(5)←CNT(5)+1 (S26), and, thus

10

X=      1  2  3  4  5  6  7  8

PNT(X)= 0  0  0  0 20  0  0  0

CNT(X)= 0  0  0  0  3  0  0  0


15  (S32) becomes Yes as PNT(X)(=0)=PNT(X+I)(=0) when X<5,

then PNT(X)←0, CNT(X)←0 (S34), while (S32) becomes No as

PNT(5)(=20)>PNT(5+I)(=0) when X=5, then PNT(5+I)←0,

CNT(5+I)←0 (S33).

(S32) becomes Yes as PNT(X)(=0)=PNT(X+I)(=0) when X>5,

20  then PNT(X)←0, CNT(X)←0 (S34).

(Any case, PNT, CNT do not change.)

(S40) becomes No as CNT(X)(=0)<3 when X<5 (PNT, CNT do

not change).

(S40) becomes Yes as CNT(5)(=3)=3 when X=5, then

25  registration (S41), then

(S42)

X=        1  2  3  4  5  6  7  8

PNT(X) = 0  0  0  0  0  0  0  0

5    CNT(X) = 0  0  0  0  0  0  0  0

(S40) becomes No as CNT(X)(=0)<3 when X>5 (PNT, CNT do
not change).

Then, the processing is continued.

10           When the target marks have an ideal
arrangement, the distances between the marks have
theoretical values.  However, actually, they may be
somewhat different from the theoretical values even when
the marks are actually the predetermined ones to be

15   recognized/detected.  The detection part 32 gives a
score on the differences from the theoretical values,
and sends them to the second scoring part 33.  In this
case, the score becomes higher as the differences from
the theoretical values becomes smaller.  For example, a

20   pattern of a regular triangle having three marks as
vertexes thereof, and each distance therebetween is 30
pixels as a length on a respective side thereof is
assumed.  Distances d1, d2 and d3 between respective
marks actually arranged are calculated, and difference

25   from the ideal distance of 30 pixels is obtained for

each side.  Then, the thus-obtained distances are summed
as D, as shown in the following formula (8):

$$D = |d1-30| + |d2-30| + |d3-30|$$
$$\cdots (8)$$

Then, based on the thus-obtained D, a score Pd is
obtained by using the following two-dimensional table 5:

Table 5 (for Pd)

| D | 0 ... 2 | 3 ... 5 | 6 ... 8 | 9 ... |
|---|---|---|---|---|
| Pd | 10 | 8 | 5 | −1 |

The second scoring part 33 sums the mark
resemblance Pel obtained by the score summarizing part
23b and the score Pd obtained by the detection part 32
so as to obtain a score Psc representing a final pattern
resemblance.  The following formula (9) is one example
of calculating the final pattern resemblance Psc:

$$Psc = \sum Pel + Pd \quad \cdots (9)$$

Where "$\sum$" means summing Pel for all the marks constitute
the pattern.

The decision part 34 determines that the
target marks are of the pattern to be
recognized/detected when the above-mentioned final
pattern resemblance Psc is higher than a predetermined
5    threshold.

Further, the present invention is not limited
to the above-described embodiments, and variations and
modifications may be made without departing from the
scope of the present invention.

10    The present application is based on Japanese
priority application No. 2001-017035, filed on January
25, 2001, the entire contents of which are hereby
incorporated by reference.